



1485H Series

4" Heavy Commercial

Thermally Improved Blind Window

1485H Series Features

PERFORMANCE

The 1485H Series fixed, projected, and casement windows exceed the performance specifications set forth in ANSI/AAMA/NWDA 101/I.S.2-97 for Architectural Windows – AW and Heavy Commercial –HC.

MAIN FRAME CONSTRUCTION

The frame material is constructed from .125" nominal wall thickness of 6063-T6 aluminum alloy and temper with a depth of 4". It features a standard equal leg. All exterior aluminum is separated from interior aluminum by ridged, structural, pour-in-place thermal barrier. All joinery of frame members is closely fit and mechanically fastened with screws. Heliarc welded frame corners are optional. All frame joinery is sealed with small joint sealant.

VENT FRAME CONSTRUCTION

All operating ventilators consist of a tubular member with .125" nominal wall thickness of 6063-T6 aluminum alloy and temper with a depth of 2". All exterior aluminum is separated from interior aluminum by ridged, structural, pour-in-place thermal barrier. Vent corners are mitered assembled by means of mechanical fastening with screws. All vent joinery is sealed with small joint sealant. Operating ventilators have a double Santoprene®, non-shrinking dual durometer, thermo plastic rubber weather-stripping around perimeter. **Optional:** Heliarc welding of sash corners and/or double corner keys and hydraulically swaged.

DUAL GLAZED HINGED ACCESS SASH (WITH or WITHOUT BLINDS)

All operating access sash consist of a tubular member with .125" nominal wall thickness of 6063-T6 aluminum alloy and temper with a depth of 1-1/4". Vent corners are mitered, assembled by means of mechanical fastening with screws. Hinged sash is supported by stainless steel four bar arms and held shut by white bronze key locks with US25D brushed finish. Operating ventilators have a double Santoprene®, non-shrinking dual durometer, thermo plastic rubber weather-stripping around perimeter.

BLINDS

Head rail is 0.625" wide x .650" high x .050" thick with bottom rail being 0.625" wide x .355" high x .050" thick of 6063-T5 extruded aluminum alloy and temper with a baked on polyester powder coat finish conforming to AAMA Specifications #603.8-1985. Ladder cord locations do not exceed 6" from the end of the slot or 24" apart. Tilt control knob is designed with a slip feature to minimize damage due to over tilting of the blind. Removable key operated knobs and angled tilt control knobs optional.

GLAZING

Windows are interior glazed with outboard lite being structurally glazed. Inboard sash is also structurally glazed. Glazing of 5/8" insulated glass on the exterior and 1/8" to 1/4" monolithic glass can be utilized. Winco recommends heat-treating for both lites of insulated glass.

SCREEN

Screen frames are fabricated from extruded 6063-T6 aluminum alloy and temper. Aluminum screen wire produced from 5154 alloy in .011 diameter with mesh 18 x 16 is standard. Charcoal Anodized and Brite Kote Aluminum are standard colors. Mesh is installed so the cloth can be easily replaced with a roll-in spline. Suitable hardware is furnished to mount on the window unit. **Optional:** Fiberglass or stainless steel with .009 diameter wire or Winco's 1000 Series hinged Security Screen with perforated steel sheet.

HARDWARE

All exposed locking hardware, strikes and keepers are solid white bronze alloy with US25D brushed finish. All four bar arms, four bar casement arms, friction adjustable H.O.A., and key release limit arms consist of stainless steel conforming to AAMA 904.1. **Optional:** Zinc die-cast with painted finish and or zinc plated steel arms. **Projected Windows** are furnished with casement locks and four bar arms. **Optional:** Key lock, under screen push bar, pivot shoe roto-operator, pull handle. **Casement Windows (out-swing)** are furnished with roto-operator, two point lock and 3-knuckle butt hinge with aluminum pin. **Optional:** Four bar casement hinge, casement lock, key lock, pull handle, 3-knuckle butt hinge with stainless steel pin, 5-knuckle butt hinge with stainless steel pin, extension hinge, emergency exit sign. **(in-swing)** are furnished with four bar casement arms two point lock and pull handle. **Drop Head In Swing Windows** are furnished with key locks hold open arms, and four bar arms. **Optional:** Casement lock, pull handle.

Santoprene is a registered trademark of Advanced Elastomer Systems.