

## PERFORMANCE

The Series 1550 window is a thermally broken mainframe and sash that exceeds the performance specification criteria as required by ANSI/AAMA for AW (Architectural Grade) windows.

Fixed		Project Out - Awning			
AAMA Rating	AW-100		AAMA Rating	AW-100	
Air Infiltration	0.01 CFM/ft <sup>2</sup>		Air Infiltration	0.01 CFM/ft <sup>2</sup>	
Water	Over 12 psf		Water	Over 12 psf	
Structural	150 psf		Structural	150 psf	
CRF (AAMA 1503)	64		CRF (AAMA 1503)	not tested	
Center of Glass U-Value	Window U-Factor <sup>3</sup>		Center of Glass U-Value	Window U-Factor <sup>3</sup>	
BTU/Ft <sup>2</sup> x F° x Hr	47" x 59" <sup>2</sup>	60" x 99" <sup>1</sup>	BTU/Ft <sup>2</sup> x F° x Hr	59" x 24" <sup>2</sup>	60" x 36" <sup>1</sup>
0.20	0.35	0.31	0.20	0.51	0.44
0.24	0.38	0.34	0.24	0.53	0.46
0.29	0.42	0.38	0.29	0.56	0.50
0.34	0.46	0.42	0.34	0.59	0.53
0.47	0.57	0.53	0.47	0.66	0.61

Project In - Hopper			Casement		
AAMA Rating	AW-100		AAMA Rating	AW-100	
Air Infiltration	0.03 CFM/ft <sup>2</sup>		Air Infiltration	0.02 CFM/ft <sup>2</sup>	
Water	Over 12 psf		Water	Over 12 psf	
Structural	150 psf		Structural	150 psf	
CRF (AAMA 1503)	not tested		CRF (AAMA 1503)	not tested	
Center of Glass U-Value	Window U-Factor <sup>3</sup>		Center of Glass U-Value	Window U-Factor <sup>3</sup>	
BTU/Ft <sup>2</sup> x F° x Hr	59" x 24" <sup>2</sup>	60" x 36" <sup>1</sup>	BTU/Ft <sup>2</sup> x F° x Hr	24" x 59" <sup>2</sup>	36" x 60" <sup>1</sup>
0.20	0.51	0.44	0.20	0.51	0.44
0.24	0.53	0.46	0.24	0.53	0.46
0.29	0.56	0.50	0.29	0.56	0.50
0.34	0.59	0.53	0.34	0.59	0.53
0.47	0.66	0.61	0.47	0.66	0.61

This Information is based on current product design, sealed dual glazing, warm edge spacers and testing standards.

Please contact WINCO for project specific information

<sup>1</sup> AAMA 101 Test Size

<sup>2</sup> NFRC Gateway Test Size

<sup>3</sup> Based on NFRC 100