

# Transira™ Motorized Shade Accessory Sash Product Information - Glass Options & Combination



## GLAZING

The windows is interior glazed with .050 thick extruded aluminum glazing beads accommodating thickness of 1/4" monolithic or 1" for Insulated Glass Unit (I.G.U.).

Dual or triple glazing are optional utilizing an interior panel sash that is hinged with 4-bar stainless steel hinges. A lift-out sash is not a feasible option due to the wiring requirements for the roller shade.

Default is a motorized roller shade with a wired connection for power & control. A solar powered wireless option is available, but has limited application options of grouping and without communication with a Building Management System (BMS).

Roller shades are the default configuration, but Venetian blinds are also available.





For actual details refer to the detail section in this Transira™ product brochure.

WINCO RESERVES THE RIGHT TO MODIFY OR CHANGE INFORMATION WITHIN THIS BOOK WHEN DEEMED NECESSARY FOR PRODUCT IMPROVEMENT

© WINCO WINDOW COMPANY, INC. 2026

## HARDWARE - Casement Configurations

All exposed locking hardware, strikes and keepers are solid white bronze alloy with US25D brushed finish. All four bar arms, casement arms, friction arms and key release limit arms are stainless steel conforming to AAMA 904.1. Five knuckle butt hinges are fabricated of 6063-T6 aluminum with nylon bushings and a stainless steel hinge pin.

	<p>Project Out Casement (POC) w/ Butt Hinges</p> <p>Butt Hinges<sup>2</sup> Stainless Steel Friction Adjuster Single Point or Multi-Point Lift Lock(s)<sup>1</sup></p>	<p><u>Optional Hardware Accessories:</u> Casement Roto Operator Access Control Lift Locks Pole Ring Lift Lock(s)<sup>1</sup> Pole Ring Non-Removable Limit Stop Key-Release Limit Stop</p>
	<p>Project Out Casement (POC) w/ Concealed Hinges</p> <p>Stainless Steel 4-Bar Casement Hinges Single Point or Multi-Point Lift Lock(s)<sup>1</sup></p>	<p><u>Optional Hardware Accessories:</u> Casement Roto Operator<sup>3</sup> Access Control Lift Locks Pole Ring Lift Lock(s)<sup>1</sup> Pole Ring Non-Removable Limit Stop Key-Release Limit Stop</p>
	<p>Project In Casement (PIC) w/ Butt Hinges</p> <p>Butt Hinges<sup>2</sup> Stainless Steel Friction Adjuster Single Point or Multi-Point Lift Lock(s)<sup>1</sup></p>	<p><u>Optional Hardware Accessories:</u> Access Control Lift Locks Pole Ring Lift Lock(s)<sup>1</sup> Pole Ring Non-Removable Limit Stop Key-Release Limit Stop</p>
	<p>Project In Casement (PIC) w/ Concealed Hinges</p> <p>Stainless Steel 4-Bar Casement Hinges Single Point or Multi-Point Lift Lock(s)<sup>1</sup></p>	<p><u>Optional Hardware Accessories:</u> Access Control Lift Locks Pole Ring Lift Lock(s)<sup>1</sup> Pole Ring Non-Removable Limit Stop Key-Release Limit Stop</p>

Please contact WINCO for project specific information

<sup>1</sup> Lock Quantity is dependent on Operable Vent Width & Height, Additional Locks can be specified, but minimum Qty is determined by WINCO Engineering

<sup>2</sup> Butt Hinge Quantity is dependent on Operable Vent Height, Additional Hinges can be specified, but minimum Qty is determined by WINCO Engineering

<sup>3</sup> Combination of Casement Roto Operator and Concealed Hinges requires minimum Operable Vent Width to accommodate Hardware